

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

Reusable, self-closing Safety Swivel Break to EN 13617-2. Designed to protect dispenser, hose assembly and car against damage caused by drive-off incidents. Stops the flow of fuel on the hose end at separation. The 'Nozzle Break' is directly fitted into the nozzle. Suitable for ZVA Slimline 2, ZVA Slimline (old) and other nozzles



HBLDF-8 Series of swivel breakaways are intended for easy installation at nozzle inlet. The compact, light weight design incorporate a 360 degree swivel rotation at both the male end and middle joint, with simple and easily re-connectable breakaway on the opposite end. The swivel breakaway will breakaway under a pull force of more than 350 lbs. Reconnection force is approximately 15 lbs.

Technical Specifications:

Body: Aluminum
 Bushing(male thread): Brass
 Seals: Viton or Buna-N for option
 Working pressure: 0.1 to 0.35 Mpa

Packing:

Carton Size: 27cm x 25cm x 27cm
 Each Carton Quantity:50 Pcs/Carton
 Each Carton Gross Weight:13.6 Kg/Carton

Ordering Specifications:

Item No.	Inlet Size and Thread Standard		Outlet Size and Thread Standard
HBLDF-801	BSPT, BSPP or NPT 1" Female	X	M34x1.5 Male
HBLDF-802	BSPT, BSPP or NPT 3/4" Female	X	M34x1.5 Male
HBLDF-803	BSPT, BSPP or NPT 1" Male	X	M34x1.5 Male
HBLDF-804	BSPT, BSPP or NPT 1" Female	X	BSPT, BSPP or NPT 1" Male
HBLDF-805	BSPT, BSPP or NPT 3/4" Female	X	BSPT, BSPP or NPT 1" Male
HBLDF-806	BSPT, BSPP or NPT 1" Male	X	BSPT, BSPP or NPT 1" Male
HBLDF-807	BSPT, BSPP or NPT 3/4" Female	X	BSPT, BSPP or NPT 3/4" Male
HBLDF-808	BSPT, BSPP or NPT 1" Female	X	BSPT, BSPP or NPT 3/4" Male
HBLDF-809	BSPT, BSPP or NPT 1" Male	X	BSPT, BSPP or NPT 3/4" Male
HBLDF-810	BSPT, BSPP or NPT 1" Female	X	M42x1.5 Male
HBLDF-811	BSPT, BSPP or NPT 1" Male	X	M42x1.5 Male

