



Technical Specifications:

Body: Aluminum
 Bushing(male thread): Brass
 Seals: Viton or Buna-N for option
 Working pressure: 0.1 to 0.35 Mpa

HBLDF-9XX Series of swivel breakaways are intended for easy installation at nozzle inlet. The compact, light weight design incorporate a 360 degree swivel rotation at both the male end and middle joint, with simple and easily re-connectable breakaway on the opposite end. The swivel breakaway will breakaway under a pull force of more than 350 lbs. Re-connection force is approximately 15 lbs.

Ordering Specifications:

Item No.	Inlet Size and Thread Standard		Outlet Size and Thread Standard
HBLDF-904	BSPT, BSPP or NPT 1" Female	X	BSPT, BSPP or NPT 1" Male
HBLDF-905	BSPT, BSPP or NPT 3/4" Female	X	BSPT, BSPP or NPT 1" Male
HBLDF-906	BSPT, BSPP or NPT 1" Male	X	BSPT, BSPP or NPT 1" Male
HBLDF-907	BSPT, BSPP or NPT 3/4" Female	X	BSPT, BSPP or NPT 3/4" Male
HBLDF-908	BSPT, BSPP or NPT 1" Female	X	BSPT, BSPP or NPT 3/4" Male
HBLDF-909	BSPT, BSPP or NPT 1" Male	X	BSPT, BSPP or NPT 3/4" Male



Packing:

1" Breakaway:
 27cm x 25cm x 27cm
 500 Pcs/Carton
 14.9 Kg/Carton

3/4" Breakaway:
 27cm x 25cm x 27cm
 50 Pcs/Carton
 13.7 Kg/Carton