

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.



The HBSKLDLF Series Breakaway Couplings are designed for quick and safe installation at the nozzle inlet. With a compact and lightweight aluminum construction, these breakaways ensure efficient protection of fuel dispensing systems. When subjected to a pull force greater than 350 lbs, the breakaway disconnects to prevent equipment damage and fuel spillage. These units are re-connectable, allowing for easy service and reduced downtime.

Technical Specifications:

Body Material: Aluminum
 Bushing Material: Aluminum
 Seal Options: Viton or Buna-N
 Working Pressure Range: 0.1 to 0.35 MPa

Key Features:

Compact and lightweight design
 High-strength aluminum body and bushing
 Breaks away at forces above 350 lbs
 Re-connectable for ease of service
 Non-swivel design
 Ideal for both new and replacement installations

Packing Details:

1" Breakaway:
 Carton Size: 38cm x 26cm x 26cm
 Quantity: 100 pcs/carton
 Gross Weight: 14.9 Kg/carton

3/4" Breakaway:
 Carton Size: 38cm x 26cm x 26cm
 Quantity: 100 Pcs/carton
 Gross Weight: 14.7 Kg/carton

Ordering Specifications:

Item No.	Female Thread Standard & Size X Male Thread Standard & Size
HBSKLDLF-1	BSPT, BSPP or NPT 1" Female X BSPT, BSPP or NPT 1" Male
HBSKLDLF-3/4	BSPT, BSPP or NPT 3/4" Female X BSPT, BSPP or NPT 3/4" Male
HBSKLDLF-1-3/4	BSPT, BSPP or NPT 1" Female X BSPT, BSPP or NPT 3/4" Male
HBSKLDLF-3/4-1	BSPT, BSPP or NPT 3/4" Female X BSPT, BSPP or NPT 1" Male

Other Similar Products:For more information or custom requirements, please contact our technical support team or sales representative.

