

---

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

---



The HB8062AL is an upgraded aluminum dust cap with a hardened roller for added durability and a painted surface for enhanced corrosion resistance. It is ideal for use with API adaptors on fuel delivery trucks that require high endurance in harsh environments.

**Technical Specifications:**

Body Material: Painted aluminum body  
Roller Material: Hardened aluminum  
Handle Material: Brass  
Pin Material: Stainless steel  
Seals: Buna-N (Viton for Option)  
Working pressure: 0 - 0.6 Mpa  
Temperature range: -20°C to +70°C  
Rust-resistant finish, long service life

**Replacement Parts Available as follows:**

Sealing gasket for HB8062AL  
Steel chain for HB8062AL

**Application:**

Widely used on fuel tanker trucks fitted with aluminum API bottom loading valves.

**More Images:**



---

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

---



HB8062BLS (Stainless Steel Type)

**Technical Specifications:**

Item No. HB8062BLS  
Diameter: 4 inch  
Body: Stainless steel  
Seals: Special gasket for Chemical Liquid  
Handle: Brass  
Pin: Stainless steel  
Working pressure: 0 to 0.6 Mpa  
Temperature range -20-+100°C



HB8062SS (Stainless Steel Type)

**Technical Specifications:**

Item No. HB8062SS  
Diameter: 4 inch  
Body: Stainless Steel 304  
Roller: Stainless Steel 304  
Seals: Viton  
Handle: Stainless Steel 304  
Pin: Stainless steel  
Working pressure: 0 to 0.6 Mpa  
Temperature range -20-+100°C



HB8062CL (Aluminum Type)

**Technical Specifications:**

Item No. HB8062CL  
Diameter: 4 inch  
Body: Aluminum  
Seals: Buna-N  
Handle: Brass  
Pin: Stainless steel  
Working pressure: 0 to 0.6 Mpa  
Temperature range -20-+70°C