

HBVR-HT Series of Vapor Recovery Couplings with Hose Tail Connector



HBVR-HT Series of Vapor Recovery Couplings are usually connected to Vapor Recovery Adaptors. By connecting this coupling to the vapor recovery adaptor, the pneumatic interlock switch on the vapor recovery adaptor will be automatically activated, causing all valves of the vapor recovery system to open. It connects to the pipeline of the oil depot, enabling vapor recovery.

Technical Specifications:

Body Material: Aluminum
 Middle Probe: Aluminum
 Handles: Brass
 Pine and Ring: Stainless steel
 Gasket: Buna-N
 Working Pressure: 0.6 Mpa

Ordering Specifications:

Item No.	Sizes
<u>HBVR-HT100-50</u>	<u>4 inch Female X 2 inch Hose Tail</u>
<u>HBVR-HT100-65</u>	<u>4 inch Female X 2.5 inch Hose Tail</u>
<u>HBVR-HT100-80</u>	<u>4 inch Female X 3 inch Hose Tail</u>
<u>HBVR-HT100-100</u>	<u>4 inch Female X 4 inch Hose Tail</u>

HBVR-HE Series of Vapor Recovery Couplings with Male Cam-lock Connector



HBVR-HE Series of Vapor Recovery Couplings are usually connected to Vapor Recovery Adaptors. By connecting this coupling to the vapor recovery adaptor, the pneumatic interlock switch on the vapor recovery adaptor will be automatically activated, causing all valves of the vapor recovery system to open. It connects to the pipeline of the oil depot, enabling vapor recovery.

Technical Specifications:

Body Material: Aluminum
 Middle Probe: Aluminum
 Handles: Brass
 Pine and Ring: Stainless steel
 Gasket: Buna-N
 Working Pressure: 0.6 Mpa

Ordering Specifications:

Item No.	Sizes
<u>HBVR-HE100-50</u>	<u>4 inch Female X 2 inch Male Cam</u>
<u>HBVR-HE100-65</u>	<u>4 inch Female X 2.5 inch Male Cam</u>
<u>HBVR-HE100-80</u>	<u>4 inch Female X 3 inch Male Cam</u>