

Add:Bali Vallage Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Aluminum Alloy One-Way Ball Valve & Top-Seal Adapter for Fuel Spill Containers



This product designed to be used in the above Spill Container, the male side can be connected with C type quick couplings, it features an aluminum alloy housing and a stainless steel ball core, offering advantages such as a compact structure, light weight, small size, and convenient use. It is equipped with a limited lever and locking devices for safety and reliability. The ball valve is widely used for opening and closing control in non-corrosive liquid transportation pipelines. The one-way ball valve is primarily used in oil depots, gas stations, oil tank trucks, and other applications.

### Ordering Specifications:

Item No.	Male Thread	Male Camlock
HBBV-T-E-01	4 inch BSPT	4 inch Male
HBBV-T-E-02	4 inch NPT	4 inch Male

## HBEBSC-P Carbon Steel Connection Pipe for Spill Container



### Ordering Specifications:

Item No.	Male Thread	x	Male Thread
HBEBSC-P-01	4 inch BSPT		4 inch BSPT
HBEBSC-P-02	4 inch NPT		4 inch NPT

## HBTFTA-100B Series of Aluminum Tight-Fill Top-Seal Adaptors



Top-Seal Adaptor threads onto the fill pipe of underground storage tanks, and are designed to mate with top-seal delivery elbows. It usually to be used together with a Top-Seal Cap and installed in spill containment manholes on the fill riser pipe from an underground fuel storage tank. They mate with the gravity drop delivery elbow on the transport truck.

### Ordering Specifications:

Item No.	Female Side Size	Male Side Size
HBTFTA-100B	4 inch NPT or BSPT Thread	4 inch Cam-lock Coupling fit for Roller-cam

### Features:

Easy installation: integral internal wrenching lugs are provided for installing in the confined space of spill containers.

Manufactured from Durable, Corrosion-Resistant Materials: Heat Treated Aluminum with oil-resistant rubber gasket. Seamlessly compatible with the HBSYWG-100 Series of Gravity Drop Top-seal Delivery Elbows.