



Technical specifications:  
Model:**HBJBZL-80-DC12V-OGM-25Q**  
**Motor Type: Brushless Explosion-Proof**  
Name: DC Electric Self-priming Oil Pump  
Flow range: 20 to 70 L/min  
Nominal diameter: 25mm / 1”  
Motor Power: 750W  
Vertical suction distance: 2-4 meters  
Horizontal head: 10 -15 meters  
Voltage: DC12V  
Temperature Range:-20°C to+60°C  
Flow Meter: Preset-able Oval Gear Type  
Flow Meter Accuracy:  $\pm 0.5\%$   
Weight:19 KGS  
Size: L 34.5 cm W:30.5 cm H:24 cm



Technical specifications:  
Model:**HBJBZL-80-DC24V-OGM-25Q**  
**Motor Type:Brushless Explosion-Proof**  
Name: DC Electric Self-priming Oil Pump  
Flow range: 20 to 70 L/min  
Nominal diameter: 25mm / 1”  
Motor Power: 750W  
Vertical suction distance: 2-4 meters  
Horizontal head: 10 -15 meters  
Voltage: DC24V  
Temperature Range:-20°C to+60°C  
Flow Meter: Preset-able Oval Gear Type  
Flow Meter Accuracy:  $\pm 0.5\%$   
Weight:19 KGS  
Size: L 34.5 cm W:30.5 cm H:24 cm



Model: **HBJBZL-300EX-12/24V-M**  
Name: Vane Pump Metering Assembly  
Flow Rate: 300 L/min, Diameter: DN50  
Vertical Suction Distance: 3 to 5 meters,  
Horizontal Head: 15 meters  
Power Supply: DC12V or DC24V Optional  
Motor Power: 1500W, (**Explosion-proof**)  
Metering Accuracy:  $\pm 0.3\%$ , Weight:67 Kgs,  
Dimensions: 63 x 60 x 43 Centimeters



Model: **HBJBZL-350EX-AC220/380-M**  
Name: Vane Pump Metering Assembly  
Flow Rate: 350 L/min, Diameter: DN50  
Vertical Suction Distance: 3 to 5 meters,  
Horizontal Head: 15 meters  
Power Supply: AC220V or AC380V 50 Hz  
Power: 2200W, (**Explosion-proof**)  
Metering Accuracy:  $\pm 0.3\%$  Weight: 88 Kgs,  
Dimensions: 68 x 62 x 44 centimeters