

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Durable All-Weather Fuel Dispenser Hose Assemblies for Gas Stations and Industrial Fueling

HAIBO Series of fuel dispenser hoses are engineered to meet the toughest fueling environments and the most demanding standards worldwide. Designed for versatility, durability, and extreme weather performance, they are suitable for retail fueling stations, commercial fleets, and industrial applications. **WITH DIFFERENT STANDARDS AS FOLLOWS: HG/T3037, UL330, EN1360, AS2683, JISK6343 ETC.**

### HG/T3037 Standard of Fuel Dispenser Hoses or Hose Assemblies (Black Color is our regular item in stock)



Series No. :**HG/T3037-3/4**  
Name: Fuel Dispenser Hose  
Nominal size: 3/4"  
Inner Diameter: 19 mm  
Outer Diameter: 30 mm  
Max. working pressure:1.6 Mpa  
Test pressure:2.4 Mpa  
Max. Bursting pressure: 4.8 Mpa  
Min. Bend radius: 100 mm  
Weight Per Meter:0.697 Kg  
**Length:60 Meters/Roll**  
Tube material: NBR  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +55°C



Series No. :**HG/T3037-7/8**  
Name: Fuel Dispenser Hose  
Nominal size: 7/8"  
Inner Diameter: 22 mm  
Outer Diameter: 31.5 mm  
Max. working pressure:1.6 Mpa  
Test pressure:2.4 Mpa  
Max. Bursting pressure: 4.8 Mpa  
Min. Bend radius: 130 mm  
Weight Per Meter:0.770 Kg  
**Length:60 Meters/Roll**  
Tube material: NBR  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +55°C



Series No. :**HG/T3037-1**  
Name: Fuel Dispenser Hose  
Nominal size: 1"  
Inner Diameter: 25 mm  
Outer Diameter: 37 mm  
Max. working pressure:1.6 Mpa  
Test pressure:2.4 Mpa  
Max. Bursting pressure: 4.8 Mpa  
Min. Bend radius: 150 mm  
Weight Per Meter:0.982 Kg  
**Length:60 Meters/Roll**  
Tube material: NBR  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +55°C



Series No. :**HG/T3037-1.25**  
Name: Fuel Dispenser Hose  
Nominal size: 1.25"  
Inner Diameter: 32 mm  
Outer Diameter: 44 mm  
Max. working pressure:1.6 Mpa  
Test pressure:2.4 Mpa  
Max. Bursting pressure: 4.8 Mpa  
Min. Bend radius: 175 mm  
Weight Per Meter:1.145 Kg  
**Length:60 Meters/Roll**  
Tube material: NBR  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +55°C



Series No. :**HG/T3037-1.5**  
Name: Fuel Dispenser Hose  
Nominal size: 1.5"  
Inner Diameter: 38 mm  
Outer Diameter: 50 mm  
Max. working pressure:1.6 Mpa  
Test pressure:2.4 Mpa  
Max. Bursting pressure: 4.8 Mpa  
Min. Bend radius: 225 mm  
Weight Per Meter:1.339 Kg  
**Length:60 Meters/Roll**  
Tube material: NBR  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +55°C

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Ordering Specifications for Hose Assemblies:

Item No.	Size	Color	Length	Coupling Types
HG/T3037-3/4-B-1.5-FS	3/4"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-B-4-FS	3/4"	Black	4 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-B-5-FS	3/4"	Black	5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-B-6-FS	3/4"	Black	6 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-B-8-FS	3/4"	Black	8 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-B-10-FS	3/4"	Black	10 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-1.5-FS	3/4"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-4-FS	3/4"	Red	4 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-5-FS	3/4"	Red	5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-6-FS	3/4"	Red	6 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-8-FS	3/4"	Red	8 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-3/4-R-10-FS	3/4"	Red	10 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-1.5-FS	1"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-4-FS	1"	Black	4 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-5-FS	1"	Black	5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-6-FS	1"	Black	6 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-8-FS	1"	Black	8 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-B-10-FS	1"	Black	10 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-1.5-FS	1"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-4-FS	1"	Red	4 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-5-FS	1"	Red	5 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-6-FS	1"	Red	6 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-8-FS	1"	Red	8 Meter	Fixed Coupling X Swivel Coupling
HG/T3037-1-R-10-FS	1"	Red	10 Meter	Fixed Coupling X Swivel Coupling

**Note:** The hose' s size, color, length, and both end fittings — including fixed and swivel couplings — as well as their thread standards, can all be customized.

### Key Features:

**Tube:** High-quality NBR (Nitrile Rubber) for excellent fuel resistance. Compatible with a wide range of fuels including gasoline, diesel, ethanol blends (E10–E85), and biodiesel blends (B20).

**Reinforcement:** Single high-tensile steel wire braid for strength and flexibility. Designed with a hardwall structure, offering low volume expansion, enhanced durability, kink resistance, and reliable conductivity for safety.

**Cover:** Durable CPE (Chlorinated Polyethylene) with superior resistance to ozone, weather, and abrasion.

**Length:** Available in bulk lengths or custom-coupled assemblies

**Color Options :** Multiple color options: Black, Red, Yellow, Blue, Green, Grey, Orange

### More Images for references:



Long Hose Assembly



Short Hose Assembly



Colorful Hose Assembly

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## HAIBO Series of Fuel Dispenser Hoses or Hose Assemblies– High Performance, All-Weather Flexibility

HAIBO Series of fuel dispenser hoses are engineered to meet the toughest fueling environments and the most demanding standards worldwide. Designed for versatility, durability, and extreme weather performance, they are suitable for retail fueling stations, commercial fleets, and industrial applications. **WITH DIFFERENT STANDARDS AS FOLLOWS: HG/T3037, UL330, EN1360, AS2683, JISK6343 ETC.**

### UL330 Standard of Fuel Dispenser Hoses or Hose Assemblies (Black Color is our regular item in stock)



Series No. :**UL330-3/4**  
Name: Fuel Dispenser Hose  
Nominal size: 3/4"  
Inner Diameter: 19 mm  
Outer Diameter: 28.5 mm  
Max. working pressure: 50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure:1000 Psi  
Min. Bend radius:  
Weight Per Meter:0.601 Kg  
**Length:60 Meters/Roll**  
Tube : Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C



Series No. :**UL330-7/8**  
Name: Fuel Dispenser Hose  
Nominal size: 7/8"  
Inner Diameter: 22 mm  
Outer Diameter: 31.5 mm  
Max. working pressure:50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure: 1000 Psi  
Min. Bend radius:  
Weight Per Meter:0.788 Kg  
**Length:60 Meters/Roll**  
Tube: Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C



Series No. :**UL330-1**  
Name: Fuel Dispenser Hose  
Nominal size: 1"  
Inner Diameter: 25 mm  
Outer Diameter: 35 mm  
Max. working pressure:50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure: 1000 Psi  
Min. Bend radius:  
Weight Per Meter:0.796Kg  
**Length:60 Meters/Roll**  
Tube : Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C



Series No. :**UL330-1.25**  
Name: Fuel Dispenser Hose  
Nominal size: 1.25"  
Inner Diameter: 32 mm  
Outer Diameter: 44 mm  
Max. working pressure:50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure: 1000 Psi  
Min. Bend radius:  
Weight Per Meter:1.171 Kg  
**Length:60 Meters/Roll**  
Tube: Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C



Series No. :**UL330-1.5**  
Name: Fuel Dispenser Hose  
Nominal size: 1.5"  
Inner Diameter: 38 mm  
Outer Diameter: 50 mm  
Max. working pressure:50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure: 1000 Psi  
Min. Bend radius:  
Weight Per Meter:1.372 Kg  
**Length:60 Meters/Roll**  
Tube: Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C



Series No. :**UL330-5/8**  
Name: Fuel Dispenser Hose  
Nominal size: 5/8"  
Inner Diameter: 16 mm  
Outer Diameter: 25.6 mm  
Max. working pressure:50 Psi  
Test pressure:250 Psi  
Max. Bursting pressure: 1000 Psi  
Min. Bend radius:  
Weight Per Meter:0.516 Kg  
**Length:60 Meters/Roll**  
Tube: Chlorinated Polyethylene  
Reinforcement:Single Wire Braid  
Cover: Chlorinated Polyethylene  
Temperature: -40°C to +70°C

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Ordering Specifications for Hose Assemblies:

Item No.	Size	Color	Length	Coupling Types
UL330-3/4-B-1.5-FS	3/4"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-B-4-FS	3/4"	Black	4 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-B-5-FS	3/4"	Black	5 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-B-6-FS	3/4"	Black	6 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-B-8-FS	3/4"	Black	8 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-B-10-FS	3/4"	Black	10 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-1.5-FS	3/4"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-4-FS	3/4"	Red	4 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-5-FS	3/4"	Red	5 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-6-FS	3/4"	Red	6 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-8-FS	3/4"	Red	8 Meter	Fixed Coupling X Swivel Coupling
UL330-3/4-R-10-FS	3/4"	Red	10 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-1.5-FS	1"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-4-FS	1"	Black	4 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-5-FS	1"	Black	5 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-6-FS	1"	Black	6 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-8-FS	1"	Black	8 Meter	Fixed Coupling X Swivel Coupling
UL330-1-B-10-FS	1"	Black	10 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-1.5-FS	1"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-4-FS	1"	Red	4 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-5-FS	1"	Red	5 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-6-FS	1"	Red	6 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-8-FS	1"	Red	8 Meter	Fixed Coupling X Swivel Coupling
UL330-1-R-10-FS	1"	Red	10 Meter	Fixed Coupling X Swivel Coupling

**Note:** The hose's size, color, length, and both end fittings — including fixed and swivel couplings — as well as their thread standards, can all be customized.

### Key Features:

**Tube:** CPE (Chlorinated Polyethylene) for excellent fuel resistance. Compatible with a wide range of fuels including gasoline, diesel, ethanol blends (E10–E85), and biodiesel blends (B20).

**Reinforcement:** Single high-tensile steel wire braid for strength and flexibility. Designed with a hardwall structure, offering low volume expansion, enhanced durability, kink resistance, and reliable conductivity for safety.

**Cover:** Durable CPE (Chlorinated Polyethylene) with superior resistance to ozone, weather, and abrasion.

**Length:** Available in bulk lengths or custom-coupled assemblies

**Color Options :** Multiple color options: Black, Red, Yellow, Blue, Green, Grey, Orange

### More Images for references:



Long Hose Assembly



Short Hose Assembly



Colorful Hose Assembly

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## HAIBO Series of Fuel Dispenser Hoses or Hose Assemblies– High Performance, All-Weather Flexibility

HAIBO Series of fuel dispenser hoses are engineered to meet the toughest fueling environments and the most demanding standards worldwide. Designed for versatility, durability, and extreme weather performance, they are suitable for retail fueling stations, commercial fleets, and industrial applications. **WITH DIFFERENT STANDARDS AS FOLLOWS: HG/T3037, UL330, EN1360, AS2683, JISK6343 ETC.**

### EN1360 Standard of Fuel Dispenser Hoses or Hose Assemblies (Black Color is our regular item in stock)



Series No. :**EN1360-3/4**  
Name: Fuel Dispenser Hose  
Nominal size: 3/4"  
Inner Diameter: 19 mm  
Outer Diameter: 29 mm  
Max. working pressure: 232 Psi  
Test pressure:348 Psi  
Max. Bursting pressure:696 Psi  
Min. Bend radius: 100 mm  
Weight Per Meter:0.478 Kg  
**Length:60 Meters/Roll**  
Tube material: Conductive NBR  
Reinforcement:Single tensile textile Braid with a copper wire for connecting two sides' fittings.  
Cover: Chlorosulfonated Polyethylene(CSM)  
Temperature: -40°C to +55°C



Series No. **EN1360-7/8**  
Name: Fuel Dispenser Hose  
Nominal size: 7/8"  
Inner Diameter: 21 mm  
Outer Diameter: 31 mm  
Max. working pressure:232 Psi  
Test pressure:348 Psi  
Max. Bursting pressure: 696 Psi  
Min. Bend radius:130 mm  
Weight Per Meter:0.488 Kg  
**Length:60 Meters/Roll**  
Tube material: Conductive NBR  
Reinforcement:Single tensile textile Braid with a copper wire for connecting two sides' fittings.  
Cover: Chlorosulfonated Polyethylene(CSM)  
Temperature: -40°C to +55°C



Series No. :**EN1360-5/8**  
Name: Fuel Dispenser Hose  
Nominal size: 5/8"  
Inner Diameter: 16 mm  
Outer Diameter: 26 mm  
Max. working pressure:232 Psi  
Test pressure:348 Psi  
Max. Bursting pressure: 696 Psi  
Min. Bend radius: 80 mm  
Weight Per Meter:0.345 Kg  
**Length:60 Meters/Roll**  
Tube material: Conductive NBR  
Reinforcement:Single tensile textile Braid with a copper wire for connecting two sides' fittings.  
Cover: Chlorosulfonated Polyethylene(CSM)  
Temperature: -40°C to +55°C



Series No. :**EN1360-1**  
Name: Fuel Dispenser Hose  
Nominal size: 1"  
Inner Diameter: 25 mm  
Outer Diameter: 35 mm  
Max. working pressure:232 Psi  
Test pressure:348 Psi  
Max. Bursting pressure: 696 Psi  
Min. Bend radius: 150 mm  
Weight Per Meter:0.617Kg  
**Length:60 Meters/Roll**  
Tube material: Conductive NBR  
Reinforcement:Single tensile textile Braid with a copper wire for connecting two sides' fittings.  
Cover: Chlorosulfonated Polyethylene(CSM)  
Temperature: -40°C to +55°C

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Ordering Specifications for Hose Assemblies:

Item No.	Size	Color	Length	Coupling Types
EN1360-3/4-B-1.5-FS	3/4"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-B-4-FS	3/4"	Black	4 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-B-5-FS	3/4"	Black	5 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-B-6-FS	3/4"	Black	6 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-B-8-FS	3/4"	Black	8 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-B-10-FS	3/4"	Black	10 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-1.5-FS	3/4"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-4-FS	3/4"	Red	4 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-5-FS	3/4"	Red	5 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-6-FS	3/4"	Red	6 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-8-FS	3/4"	Red	8 Meter	Fixed Coupling X Swivel Coupling
EN1360-3/4-R-10-FS	3/4"	Red	10 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-1.5-FS	1"	Black	1.5 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-4-FS	1"	Black	4 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-5-FS	1"	Black	5 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-6-FS	1"	Black	6 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-8-FS	1"	Black	8 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-B-10-FS	1"	Black	10 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-1.5-FS	1"	Red	1.5 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-4-FS	1"	Red	4 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-5-FS	1"	Red	5 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-6-FS	1"	Red	6 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-8-FS	1"	Red	8 Meter	Fixed Coupling X Swivel Coupling
EN1360-1-R-10-FS	1"	Red	10 Meter	Fixed Coupling X Swivel Coupling

**Note:** The hose's size, color, length, and both end fittings — including fixed and swivel couplings — as well as their thread standards, can all be customized. Note: For higher pressure, heavy-duty, or extended service life applications, we can customize hoses with two layers of textile braid reinforcement and copper wire upon request.

## Key Features

**Conductive NBR Inner Tube:** Specially designed for safe fuel dispensing, offering excellent oil resistance and static conductivity.

**Textile Braid Reinforcement:** Single layer of high-tensile strength fiber ensures flexibility and reliable performance in daily use.

**Copper Wire Integrated:** Provides continuous electrical conductivity between both end fittings, ensuring static discharge protection.

**Durable CSM Cover:** Chlorosulfonated Polyethylene (CSM) offers outstanding resistance to weathering, ozone, abrasion, and light cracking.

**Length:** Available in bulk lengths or custom-coupled assemblies

**Color Options :** Multiple color options: Black, Red, Yellow, Blue, Green, Grey, Orange

## More Images for references:



Long Hose Assembly



Short Hose Assembly



Colorful Hose Assembly

HB Equipment shall be used in compliance with applicable country, province and local laws and regulations. Products selection shall be based on physical specifications and limitations and compatibility with the environment.