

High-Performance Brass Check Valve and Triangle Flange Connection Kit



Materials:

Main Body: Brass
Valve Disc: Brass
Flange:Triangle Type
Seals: Brass Metal-to-Metal Sealing
Connecting Gasket:With or not with for option
Medium: Gasoline, diesel ,or kerosene
Operating Temperature:-30°C ~ +55°C
Diameter: 1 inch

It is installed in the pipe line under the fueling dispenser, with check valve design which can be used in applications where the fuel dispenser need a maintenance .The Quality is 100% Factory Tested.

HBZY-4 Triangle Type Connecting Flange



Materials:

Main Body: Carbon Steel
Flange:Triangle Type
Connecting Gasket:With or not with for option
Medium: Gasoline, diesel ,or kerosene
Flange thickness: 23 mm
Hole to hole distance: 68 mm
Inner thread diameter:45 mm
Bolt hole diameter 12 mm

It is installed in the pipe line under the fueling dispenser, with triangle flange design which can be used in applications where the fuel dispenser need a maintenance .The Quality is 100% Factory Tested.

HBTFG-GASKET Triangle Flange Gasket



Triangle Flange Gasket are used for sealing of Triangle Flange Connection of Bellow Pipes, Aluminum Triangle Ball Valve & Triangular Check Valve etc..