

## **SY-JP02 Series Non-Explosion-Proof Electric Preset Diesel Metering Pump System with Hose Reel**

SY-JP02 Series of Electric Transfer Pump Assembly with Hose Reel is generally combined with AC220V /DC12V /DC24V Self-priming diesel transfer pump, 1 inch Presettable Flow Meter, 15 Meters of 3/4 inch delivery rubber hose on the hose reel, 1 inch filter, 3/4 inch automatic shutoff fuel nozzle with 360 degree nozzle swivel. Easy installation, low operating cost, small size.



Have following regular items:

1. SY-JP02-60-DC12V(Power of 550W )
2. SY-JP02-60-DC24V(Power of 550W )
3. SY-JP02-60-AC220V(Power of 550W )

Technical specifications:

Flow Meter Accuracy:±0.5%

Flow Meter: 1 inch Presettable Oval Gear Flow Meter

Flow Range:40 to 60 L/min

Pump inlet and outlet: 1 inch

Delivery Hose: 10 Meters of 1 inch hose

Nozzle:3/4 inch HB11A-60 Auto. Nozzle

Voltage: AC220V/DC12V/DC24V for option

**Very Important:** They are for fueling diesel, Kerosene, not for gasoline. The use of gasoline and the using for low-ignition point medium is strictly prohibited!