
Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

M-XXLPG Series Precision Positive Displacement Flow Meter - LPG & Refrigerant Applications

M-XX series meter is positive displacement meter for liquids. They are designed for liquid metering both in transfer and process control applications. Thanks to their design they are easy to keep and can suit a wide range of applications. The meter consists of a housing where two bladed displacement rotors and a central single blocking rotor turn in synchronized relationship within three cylindrical bores with no metal-to-metal contact within the meter element. Each rotor is supported on either end by a bearing plate through which the rotor shafts protrude.

The bladed displacement rotors, alternately move through the two half-cylinder bores of the meter element, while the single blocking rotor rotates within its bore in such a way as to produce a continuous capillary seal between the unmetered upstream product and the metered, downstream product. At one end of each rotor shaft is a timing gear. The blocking rotor gear, having twice the number of teeth of each of the displacement rotor gears, rotates at half the RPM of the displacement rotors.



M-XXLPG Positive Displacement Flow Meter including following equipment:

1. Meter Body
2. Strainer
3. Air Eliminator
4. Mechanical Register
5. Differential Valve

Class 10 Application: used for liquefied petroleum gas(LPG) including butane, isobutene, pentane, ethane, freons and propane.

Technical Specification:

Model No	M-50LPG
Body Material	Aluminum
Accuracy	±0.2%
Flow Range	38-550L/min
Inlet/Outlet	2"

Note: When placing an order with us, please inform us what liquid the flow meter will be used for, the working pressure and working temperature, so that we can provide the correct additional equipment for this flow meter.

Application:

Class 10 liquefied petroleum gas(LPG) including butane, isobutene, pentane, ethane, freons and propane.