

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

Stainless Steel Electric Self-Priming Pump - Industrial & AdBlue Transfer Solution



Technical specifications:

Model: **YBZYB-40-AC220V**
Name: Electric Self-priming Pump
Pump Head Material: Stainless Steel 304
Flow range: 20 to 40 L/min
Nominal diameter: 20mm / 3/4" BSPT Female
Motor Power: 200W
Vertical suction distance: 3-5meters
Horizontal head: 5 to10 meters
Power supply: AC220V 50 Hz,
Temperature Range:-20°C to+60°C



Technical specifications:

Model: **YBZYB-40-DC12V**
Name: Electric Self-priming Pump
Pump Head Material: Stainless Steel 304
Flow range: 20 to 40 L/min
Nominal diameter: 20mm / 3/4" BSPT Female
Motor Power: 155W
Vertical suction distance: 2-4meters
Horizontal head: 5 to10 meters
Power supply: DC12V
Temperature Range:-20°C to+60°C



Technical specifications:

Model: **YBZYB-40-DC24V**
Name: Electric Self-priming Pump
Pump Head Material: Stainless Steel 304
Flow range: 20 to 40 L/min
Nominal diameter: 20mm / 3/4" BSPT Female
Motor Power: 175W
Vertical suction distance: 2.5-4.5meters
Horizontal head: 5 to10 meters
Power supply: DC12V
Temperature Range:-20°C to+60°C



Technical specifications:

Model: **YBS-70-AC220**
Name: Electric Self-priming Pump
Pump Head Material: Stainless Steel 304
Flow range: 60 to 70 L/min
Nominal diameter: 1" BSPT Female
Motor Power: 550W
Vertical suction distance: 3-5meters
Horizontal head: 5 to10 meters
Power supply: AC220V 50 Hz
Temperature Range:-20°C to+60°C
CAN BE USED FOR AD-BLUE LIQUID